

# Product datasheet

Specifications



## APC Easy UPS BVX 2200VA, 230V, AVR, India Sockets

BVX2200LI-IN

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
Rated Power In W	1200 W
Rated Power In Va	2200 VA
Output Connection Type	5 India 3-pin 6A
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Battery Voltage	24 V
Battery Capacity	9 Ah
Extended Runtime	0
Replacement Battery	<a href="#">APCRBC177</a>

### General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No
Ups Size	WS

## Physical

Colour	Black
Height	19.0 cm
Width	14.0 cm
Depth	39.0 cm
Net Weight	12.2 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	40...70 Hz +/- 5 Hz auto-sensing
Plug Standard	India 3-pin 16A
Input Voltage Limits	140...300 V
Input Protection Type	Circuit breaker

## Output

Maximum Configurable Power In W	1200 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Graph Display	1
Maximum Configurable Power In Va	2200 VA
Transfer Time	6 ms typical : 10 ms maximum

## Conformance

Product Certifications	BIS
------------------------	-----

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

## Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

---

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

---

## Surge Protection and Filtering

---

<b>Surge Energy Rate</b>	255 J
--------------------------	-------

---

## Packing Units

---

<b>Unit Type Of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number Of Units In Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	29.7 cm
-------------------------	---------

---

<b>Package 1 Width</b>	49.5 cm
------------------------	---------

---

<b>Package 1 Length</b>	23.5 cm
-------------------------	---------

---

<b>Package 1 Weight</b>	13.2 kg
-------------------------	---------

---

## Contractual warranty

---

<b>Warranty</b>	2 Years on UPS & 1 Year on Battery
-----------------	------------------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Weeee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)